



CB-51 Bullet camera

CB-51 (Bullet camera)	
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS
Lens	2.8mm@F1.6
Angle Of View (H)	112.9°
Angle Of View (V)	59.1°
Angle Of View (O)	121.2°
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 50m (164ft) IR range
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	H.265
Frame Rate	15 FPS (recommended) to 25 FPS (2880 x 1620)
Audio	
Supported	Yes
Certifications	
Certifications	UL: UL60950-1 FCC: FCC Part 15

General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 6.0W
Dimensions (L × W × H)	190×73×71mm (7.5"×2.9"×2.8")
Net Weight	0.45kg (0.99lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
ONVIF and NDAA	Yes