



CB-82 4K Bullet with Zoom

CB-82 (8MP Bullet 2.8 ~ 12mm)	
Sensor	1/2.8", 8.0 megapixel, progressive scan, CMOS
Lens Type	2.8 ~ 12mm
Field of View (H)	107.4° ~ 29.2°
Field of View (V)	54.2° ~ 16.3°
Field of View (D)	111.0° ~ 33.1°
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 50m (164ft)
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	15 FPS (recommended) to 20 FPS (3840 x 2160)
Audio	
Supported	Yes
Certifications	
Protection	IP67

General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 10.5W
Dimensions (L × W × H)	245 × 86 × 72mm (9.6" × 3.4" × 2.8")
Weight	0.92kg (2.03lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
ONVIF and NDAA	Yes