



CD-52 5MP Dome with Zoom

CD-52 (5MP Dome with Zoom 2.8 ~ 12mm)	
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS
Lens	2.8 ~ 12mm, AF automatic focusing and motorized zoom lens
Angle Of View (H)	96.4°~32.7°
Angle Of View (V)	51.3°~18.6°
Angle Of View (O)	101.2°~37.2°
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 40m (131ft) IR range
Defog	Digital Defog
WDR	120dB
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
Frame Rate	15 FPS (recommended) to 25 FPS (2880 x 1620)
Audio	
Supported	Yes
Certifications	
Certifications	UL: UL 62368-1

General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 8.0W
Dimensions (Ø x H)	Φ128mmx100mm (Ø5.0" x 3.9")
Net Weight	0.66kg (1.46lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
ONVIF and NDAA	Yes