



CD-81 4K Dome

| CD-81 (8MP Dome camera) | |
|--------------------------|---|
| Sensor | 1/2.7", 8.0 megapixel, progressive scan, CMOS |
| Lens | 2.8mm @F1.6 |
| Angle Of View (H) | 112.9° |
| Angle Of View (V) | 59.1° |
| Angle Of View (O) | 121.2° |
| Day/Night | IR-cut filter with auto switch (ICR) |
| IR Range | Up to 30m (98ft) IR range |
| Defog | Digital Defog |
| WDR | 120dB |
| Video | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG |
| Frame Rate | 15 FPS (recommended) to 20 FPS (3840 x 2160) |
| Audio | |
| Supported | Yes |
| Certifications | |
| Certifications | UL: UL 62368-1, 2nd Ed. |

| General | |
|---------------------|--|
| Power | DC 12V±25%, PoE (IEEE 802.3af) |
| | Power consumption: Max 4.5W |
| Dimensions (Ø x H) | Φ109 x 83mm (Ø4.3" x 3.3") |
| Net Weight | 0.37kg (0.82lb) |
| Working Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Surge Protection | 4KV |
| Ingress Protection | IP67 |
| Vandal Resistant | IK10 |
| ONVIF and NDAA | Yes |